

**PUNTRICIA D INVERTER**  
**INVERTER SPOT WELDERS**

SALDATRICI A PUNTI  
**TRE CI**



#### Technical data

*It may change without forewarning*

FEEDING	3x400 V – 50/60 Hz
MAXIMUM INTENSITY	5000 Amp. by module
FREQUENCY	20 KHz.
DUTY CYCLE	15%
CONTROL SYSTEM	COSTANT CURRENT
PROGRAMS	32 calling from pannel or other signals
INPUT SIGNALS	Program selection of welding;Start cycle, weld/no weld, program blocking, reset alarms.
INPUT CONTACTS	without tension or transistor
OUTPUT SIGNALS	END CYCLE, WELD GO/NO GO
OUTPUT CONTACTS	MOSFET (100AQC, 150 mA )
WORKING TEMPERATURE	0 – 45°



**TRE.CI srl** Via Cascina del Sole, 70/a .  
20026 NOVATE MILANESE - MILANO  
tel. +39.023511869 - fax +39.0233260329  
www.tre-ci.com email: info@tre-ci.com



**TRE.CI srl** Via Cascina del Sole, 70/a .  
20026 NOVATE MILANESE - MILANO  
tel. +39.023511869 - fax +39.0233260329  
www.tre-ci.com email: info@tre-ci.com